

NAME

diagnostics, splain – produce verbose warning diagnostics

SYNOPSIS

Using the `diagnostics` pragma:

```
use diagnostics;
use diagnostics -verbose;

enable diagnostics;
disable diagnostics;
```

Using the `splain` standalone filter program:

```
perl program 2>diag.out
splain [-v] [-p] diag.out
```

Using `diagnostics` to get stack traces from a misbehaving script:

```
perl -Mdiagnostics=--traceonly my_script.pl
```

DESCRIPTION**The `diagnostics` Pragma**

This module extends the terse diagnostics normally emitted by both the perl compiler and the perl interpreter (from running perl with a `-w` switch or `use warnings`), augmenting them with the more explicative and endearing descriptions found in `perldiag`. Like the other pragmata, it affects the compilation phase of your program rather than merely the execution phase.

To use in your program as a pragma, merely invoke

```
use diagnostics;
```

at the start (or near the start) of your program. (Note that this *does* enable perl's `-w` flag.) Your whole compilation will then be subject(ed :-)) to the enhanced diagnostics. These still go out `STDERR`.

Due to the interaction between runtime and compiletime issues, and because it's probably not a very good idea anyway, you may not use `no diagnostics` to turn them off at compiletime. However, you may control their behaviour at runtime using the `disable()` and `enable()` methods to turn them off and on respectively.

The `-verbose` flag first prints out the [perldiag\(1\)](#) introduction before any other diagnostics. The `$diagnostics::PRETTY` variable can generate nicer escape sequences for pagers.

Warnings dispatched from perl itself (or more accurately, those that match descriptions found in `perldiag`) are only displayed once (no duplicate descriptions). User code generated warnings a la `warn()` are unaffected, allowing duplicate user messages to be displayed.

This module also adds a stack trace to the error message when perl dies. This is useful for pinpointing what caused the death. The `-traceonly` (or just `-t`) flag turns off the explanations of warning messages leaving just the stack traces. So if your script is dieing, run it again with

```
perl -Mdiagnostics=--traceonly my_bad_script
```

to see the call stack at the time of death. By supplying the `-warntrace` (or just `-w`) flag, any warnings emitted will also come with a stack trace.

The `splain` Program

While apparently a whole nuther program, `splain` is actually nothing more than a link to the (executable) `diagnostics.pm` module, as well as a link to the `diagnostics.pod` documentation. The `-v` flag is like the `use diagnostics -verbose` directive. The `-p` flag is like the `$diagnostics::PRETTY` variable. Since you're post-processing with `splain`, there's no sense in being able to `enable()` or `disable()` processing.

Output from `splain` is directed to `STDOUT`, unlike the pragma.

EXAMPLES

The following file is certain to trigger a few errors at both runtime and compiletime:

```
use diagnostics;
print NOWHERE "nothing\n";
print STDERR "\n\tThis message should be unadorned.\n";
warn "\tThis is a user warning";
print "\nDIAGNOSTIC TESTER: Please enter a <CR> here: ";
my $a, $b = scalar <STDIN>;
print "\n";
print $x/$y;
```

If you prefer to run your program first and look at its problem afterwards, do this:

```
perl -w test.pl 2>test.out
./splain < test.out
```

Note that this is not in general possible in shells of more dubious heritage, as the theoretical

```
(perl -w test.pl >/dev/tty) >& test.out
./splain < test.out
```

Because you just moved the existing **stdout** to somewhere else.

If you don't want to modify your source code, but still have on-the-fly warnings, do this:

```
exec 3>&1; perl -w test.pl 2>&1 1>&3 3>&- | splain 1>&2 3>&-
```

Nifty, eh?

If you want to control warnings on the fly, do something like this. Make sure you do the use first, or you won't be able to get at the **enable()** or **disable()** methods.

```
use diagnostics; # checks entire compilation phase
print "\ntime for 1st bogus diags: SQUAWKINGS\n";
print BOGUS1 'nada';
print "done with 1st bogus\n";

disable diagnostics; # only turns off runtime warnings
print "\ntime for 2nd bogus: (squelched)\n";
print BOGUS2 'nada';
print "done with 2nd bogus\n";

enable diagnostics; # turns back on runtime warnings
print "\ntime for 3rd bogus: SQUAWKINGS\n";
print BOGUS3 'nada';
print "done with 3rd bogus\n";

disable diagnostics;
print "\ntime for 4th bogus: (squelched)\n";
print BOGUS4 'nada';
print "done with 4th bogus\n";
```

INTERNALS

Diagnostic messages derive from the *perldiag.pod* file when available at runtime. Otherwise, they may be embedded in the file itself when the splain package is built. See the *Makefile* for details.

If an extant `$_SIG{__WARN__}` handler is discovered, it will continue to be honored, but only after the **diagnostics::splainthis()** function (the module's `$_SIG{__WARN__}` interceptor) has had its way with your warnings.

There is a `$diagnostics::DEBUG` variable you may set if you're desperately curious what sorts of things are being intercepted.

```
BEGIN { $diagnostics::DEBUG = 1 }
```

BUGS

Not being able to say “no diagnostics” is annoying, but may not be insurmountable.

The `-pretty` directive is called too late to affect matters. You have to do this instead, and *before* you load the module.

```
BEGIN { $diagnostics::PRETTY = 1 }
```

I could start up faster by delaying compilation until it should be needed, but this gets a “panic: top_level” when using the pragma form in Perl 5.001e.

While it’s true that this documentation is somewhat subserious, if you use a program named *splain*, you should expect a bit of whimsy.

AUTHOR

Tom Christiansen <tchrist@mox.perl.com>, 25 June 1995.