

NAME

perlivp – Perl Installation Verification Procedure

SYNOPSIS

```
perlivp [-p] [-v] [-h]
```

DESCRIPTION

The **perlivp** program is set up at Perl source code build time to test the Perl version it was built under. It can be used after running:

```
make install
```

(or your platform’s equivalent procedure) to verify that **perl** and its libraries have been installed correctly. A correct installation is verified by output that looks like:

```
ok 1
ok 2
```

etc.

OPTIONS

-h help

Prints out a brief help message.

-p print preface

Gives a description of each test prior to performing it.

-v verbose

Gives more detailed information about each test, after it has been performed. Note that any failed tests ought to print out some extra information whether or not **-v** is thrown.

DIAGNOSTICS

- print “# Perl binary ‘\$perlpath’ does not appear executable.\n”;
Likely to occur for a perl binary that was not properly installed. Correct by conducting a proper installation.
- print “# Perl version ‘\$J’ installed, expected \$ivp_VERSION.\n”;
Likely to occur for a perl that was not properly installed. Correct by conducting a proper installation.
- print “# Perl \@INC directory ‘\$’ does not appear to exist.\n”;
Likely to occur for a perl library tree that was not properly installed. Correct by conducting a proper installation.
- print “# Needed module ‘\$’ does not appear to be properly installed.\n”;
One of the two modules that is used by [perlivp\(1\)](#) was not present in the installation. This is a serious error since it adversely affects perlivp’s ability to function. You may be able to correct this by performing a proper perl installation.
- print “# Required module ‘\$’ does not appear to be properly installed.\n”;
An attempt to `eval "require $module"` failed, even though the list of extensions indicated that it should succeed. Correct by conducting a proper installation.
- print “# Unnecessary module ‘bLuRfle’ appears to be installed.\n”;
This test not coming out ok could indicate that you have in fact installed a bLuRfle.pm module or that the `eval " require \"$module_name.pm\"; "` test may give misleading results with your installation of perl. If yours is the latter case then please let the author know.
- print “# file”,+(\$#missing == 0) ? ” : ’s’,“ missing from installation:\n”;
One or more files turned up missing according to a run of `ExtUtils::Installed -> validate()` over your installation. Correct by conducting a proper installation.

For further information on how to conduct a proper installation consult the `INSTALL` file that comes with the perl source and the `README` file for your platform.

AUTHOR

Peter Prymmer