

NAME

postlog – Postfix–compatible logging utility

SYNOPSIS

postlog [**-iv**] [**-c config_dir**] [**-p priority**] [**-t tag**] [*text...*]

DESCRIPTION

The **postlog(1)** command implements a Postfix–compatible logging interface for use in, for example, shell scripts.

By default, **postlog(1)** logs the *text* given on the command line as one record. If no *text* is specified on the command line, **postlog(1)** reads from standard input and logs each input line as one record.

By default, logging is sent to **syslogd(8)** or **postlogd(8)**; when the standard error stream is connected to a terminal, logging is sent there as well.

The following options are implemented:

-c config_dir

Read the **main.cf** configuration file in the named directory instead of the default configuration directory.

-i (obsolete)

Include the process ID in the logging tag. This flag is ignored as of Postfix 3.4, where the PID is always included.

-p priority (default: **info**)

Specifies the logging severity: **info**, **warn**, **error**, **fatal**, or **panic**. With Postfix 3.1 and later, the program will pause for 1 second after reporting a **fatal** or **panic** condition, just like other Postfix programs.

-t tag Specifies the logging tag, that is, the identifying name that appears at the beginning of each logging record. A default tag is used when none is specified.

-v Enable verbose logging for debugging purposes. Multiple **-v** options make the software increasingly verbose.

ENVIRONMENT

MAIL_CONFIG

Directory with the **main.cf** file.

CONFIGURATION PARAMETERS

The following **main.cf** parameters are especially relevant to this program.

The text below provides only a parameter summary. See **postconf(5)** for more details including examples.

config_directory (see 'postconf -d' output)

The default location of the Postfix main.cf and master.cf configuration files.

import_environment (see 'postconf -d' output)

The list of environment parameters that a privileged Postfix process will import from a non–Postfix parent process, or name=value environment overrides.

syslog_facility (mail)

The syslog facility of Postfix logging.

syslog_name (see 'postconf -d' output)

A prefix that is prepended to the process name in syslog records, so that, for example, "smtpd" becomes "prefix/smtpd".

Available in Postfix 3.4 and later:

maillog_file (empty)

The name of an optional logfile that is written by the Postfix **postlogd(8)** service.

postlog_service_name (postlog)

The name of the [postlogd\(8\)](#) service entry in master.cf.

SEE ALSO

[postconf\(5\)](#),
configuration parameters
[postlogd\(8\)](#),
Postfix logging
[syslogd\(8\)](#), system logging

LICENSE

The Secure Mailer license must be distributed with this software.

AUTHOR(S)

Wietse Venema
IBM T.J. Watson Research
P.O. Box 704
Yorktown Heights, NY 10598, USA

Wietse Venema
Google, Inc.
111 8th Avenue
New York, NY 10011, USA