

NAME

rmdir – remove empty directories

SYNOPSIS

rmdir [*OPTION*]... *DIRECTORY*...

DESCRIPTION

Remove the *DIRECTORY*(ies), if they are empty.

--ignore-fail-on-non-empty

ignore each failure that is solely because a directory
is non-empty

-p, --parents

remove *DIRECTORY* and its ancestors; e.g., 'rmdir **-p** a/b/c' is similar to 'rmdir a/b/c a/b a'

-v, --verbose

output a diagnostic for every directory processed

--help display this help and exit**--version**

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report rmdir translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

[rmdir\(2\)](#)

Full documentation at: <<https://www.gnu.org/software/coreutils/rmdir>>
or available locally via: info '(coreutils) rmdir invocation'