

NAME

ssh-argv0 — replaces the old ssh command-name as hostname handling

SYNOPSIS

```
hostname | user@hostname [-l login_name] [command]
hostname | user@hostname [-afgknqstvxACNTX1246] [-b bind_address]
[-c cipher_spec] [-e escape_char] [-i identity_file] [-l login_name]
[-m mac_spec] [-o option] [-p port] [-F configfile] [-L port:host:hostport] [-R
port:host:hostport] [-D port] [command]
```

DESCRIPTION

ssh-argv0 replaces the old ssh command-name as hostname handling. If you link to this script with a hostname then executing the link is equivalent to having executed ssh with that hostname as an argument. All other arguments are passed to ssh and will be processed normally.

OPTIONS

See [ssh\(1\)](#).

FILES

See [ssh\(1\)](#).

AUTHORS

OpenSSH is a derivative of the original and free ssh 1.2.12 release by Tatu Ylonen. Aaron Campbell, Bob Beck, Markus Friedl, Niels Provos, Theo de Raadt and Dug Song removed many bugs, re-added newer features and created OpenSSH. Markus Friedl contributed the support for SSH protocol versions 1.5 and 2.0. Jonathan Amery wrote this ssh-argv0 script and the associated documentation.

SEE ALSO

[ssh\(1\)](#)