

NAME

drem, dremf, dreml, remainder, remainderf, remainderl – floating-point remainder function

SYNOPSIS

```
#include <math.h>

/* The C99 versions */
double remainder(double x, double y);
float remainderf(float x, float y);
long double remainderl(long double x, long double y);

/* Obsolete synonyms */
double drem(double x, double y);
float dremf(float x, float y);
long double dreml(long double x, long double y);
```

Link with `-lm`.

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

```
remainder():
    _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L || _XOPEN_SOURCE >= 500 || /* Since
    glibc 2.19: */ _DEFAULT_SOURCE || /* Glibc versions <= 2.19: */ _BSD_SOURCE ||
    _SVID_SOURCE
remainderf(), remainderl():
    _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L || /* Since glibc 2.19: */ _DE-
    FAULT_SOURCE || /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
drem(), dremf(), dreml():
    /* Since glibc 2.19: */ _DEFAULT_SOURCE || /* Glibc versions <= 2.19: */ _BSD_SOURCE ||
    _SVID_SOURCE
```

DESCRIPTION

These functions compute the remainder of dividing x by y . The return value is $x - n * y$, where n is the value x/y , rounded to the nearest integer. If the absolute value of $x - n * y$ is 0.5, n is chosen to be even.

These functions are unaffected by the current rounding mode (see [fenv\(3\)](#)).

The `drem()` function does precisely the same thing.

RETURN VALUE

On success, these functions return the floating-point remainder, $x - n * y$. If the return value is 0, it has the sign of x .

If x or y is a NaN, a NaN is returned.

If x is an infinity, and y is not a NaN, a domain error occurs, and a NaN is returned.

If y is zero, and x is not a NaN, a domain error occurs, and a NaN is returned.

ERRORS

See [math_error\(7\)](#) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: x is an infinity and y is not a NaN

`errno` is set to **EDOM** (but see [BUGS](#)). An invalid floating-point exception (**FE_INVALID**) is raised.

These functions do not set `errno` for this case.

Domain error: y is zero

`errno` is set to **EDOM**. An invalid floating-point exception (**FE_INVALID**) is raised.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
drem() , dremf() , dreml() , remainder() , remainderf() , remainderl()	Thread safety	MT-Safe

CONFORMING TO

The functions **remainder()**, **remainderf()**, and **remainderl()** are specified in C99, POSIX.1-2001, and POSIX.1-2008.

The function **drem()** is from 4.3BSD. The *float* and *long double* variants **dremf()** and **dreml()** exist on some systems, such as Tru64 and glibc2. Avoid the use of these functions in favor of **remainder()** etc.

BUGS

Before glibc 2.15, the call

```
remainder(nan(""), 0);
```

returned a NaN, as expected, but wrongly caused a domain error. Since glibc 2.15, a silent NaN (i.e., no domain error) is returned.

Before glibc 2.15, *errno* was not set to **EDOM** for the domain error that occurs when *x* is an infinity and *y* is not a NaN. *errno* was not set

EXAMPLE

The call "remainder(29.0, 3.0)" returns -1.

SEE ALSO

[div\(3\)](#), [fmod\(3\)](#), [remquo\(3\)](#)

COLOPHON

This page is part of release 4.16 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.