

**NAME**

undocumented – undocumented library functions

**SYNOPSIS**

Undocumented library functions

**DESCRIPTION**

This man page mentions those library functions which are implemented in the standard libraries but not yet documented in man pages.

**Solicitation**

If you have information about these functions, please look in the source code, write a man page (using a style similar to that of the other Linux section 3 man pages), and send it to [mtk.manpages@gmail.com](mailto:mtk.manpages@gmail.com) for inclusion in the next man page release.

**The list**

authdes\_create(3), authdes\_getucred(3), authdes\_pk\_create(3), clntunix\_create(3), creat64(3), dn\_skipname(3), fcrypt(3), fp\_nquery(3), fp\_query(3), fp\_resstat(3), freading(3), freopen64(3), fseeko64(3), ftello64(3), ftw64(3), fwscanf(3), [get\\_avphys\\_pages\(3\)](#), getdirentries64(3), getmsg(3), getnetname(3), [get\\_phys\\_pages\(3\)](#), getpublickey(3), getsecretkey(3), h\_errlist(3), host2netname(3), hostalias(3), inet\_nsap\_addr(3), inet\_nsap\_ntoa(3), init\_des(3), libc\_nls\_init(3), mstats(3), netname2host(3), netname2user(3), nlist(3), obstack\_free(3), parse\_printf\_format(3), p\_cdbname(3), p\_cdnname(3), p\_class(3), p\_fqname(3), p\_option(3), p\_query(3), printf\_size(3), printf\_size\_info(3), p\_rr(3), p\_time(3), p\_type(3), putlong(3), putshort(3), re\_compile\_fastmap(3), re\_compile\_pattern(3), register\_printf\_function(3), re\_match(3), re\_match\_2(3), re\_rx\_search(3), re\_search(3), re\_search\_2(3), re\_set\_registers(3), re\_set\_syntax(3), res\_send\_setqhook(3), res\_send\_setrhook(3), ruserpass(3), setfileno(3), sethostfile(3), svc\_exit(3), svcudp\_enablecache(3), tell(3), tr\_break(3), tzset-wall(3), ufc\_dofinalperm(3), ufc\_doit(3), user2netname(3), wcschrnul(3), wcsftime(3), wscanf(3), xdr\_authdes\_cred(3), xdr\_authdes\_verf(3), xdr\_cryptkeyarg(3), xdr\_cryptkeyres(3), xdr\_datum(3), xdr\_des\_block(3), xdr\_domainname(3), xdr\_geteredres(3), xdr\_keybuf(3), xdr\_keystatus(3), xdr\_mapname(3), xdr\_netnamestr(3), xdr\_netobj(3), xdr\_passwd(3), xdr\_peername(3), xdr\_rmt-call\_args(3), xdr\_rmtcallres(3), xdr\_unixcred(3), xdr\_yp\_buf(3), xdr\_yp\_inaddr(3), xdr\_yp-bind\_binding(3), xdr\_ypbind\_resp(3), xdr\_ypbind\_resptype(3), xdr\_ypbind\_setdom(3), xdr\_ypdelete\_args(3), xdr\_ypmaplist(3), xdr\_ypmaplist\_str(3), xdr\_yppasswd(3), xdr\_ypreq\_key(3), xdr\_ypreq\_nokey(3), xdr\_ypresp\_all(3), xdr\_ypresp\_all\_seq(3), xdr\_ypresp\_key\_val(3), xdr\_ypresp\_maplist(3), xdr\_ypresp\_master(3), xdr\_ypresp\_order(3), xdr\_ypresp\_val(3), xdr\_yp-stat(3), xdr\_ypupdate\_args(3), yp\_all(3), yp\_bind(3), yperr\_string(3), yp\_first(3), yp\_get\_default\_domain(3), yp\_maplist(3), yp\_master(3), yp\_match(3), yp\_next(3), yp\_order(3), ypprot\_err(3), yp\_un-bind(3), yp\_update(3)

**COLOPHON**

This page is part of release 4.16 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.