

NAME

wcstoimax, wcstoumax – convert wide-character string to integer

SYNOPSIS

```
#include <stddef.h>
#include <inttypes.h>

intmax_t wcstoimax(const wchar_t *nptr, wchar_t **endptr, int base);
uintmax_t wcstoumax(const wchar_t *nptr, wchar_t **endptr, int base);
```

DESCRIPTION

These functions are just like [wcstol\(3\)](#) and [wcstoul\(3\)](#), except that they return a value of type *intmax_t* and *uintmax_t*, respectively.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

Interface	Attribute	Value
<code>wcstoimax()</code> , <code>wcstoumax()</code>	Thread safety	MT-Safe locale

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

[imaxabs\(3\)](#), [imaxdiv\(3\)](#), [strtoimax\(3\)](#), [strtoumax\(3\)](#), [wcstol\(3\)](#), [wcstoul\(3\)](#)

COLOPHON

This page is part of release 4.16 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.