

NAME

CMS_get0_type, CMS_set1_eContentType, CMS_get0_eContentType, CMS_get0_content – get and set CMS content types and content

SYNOPSIS

```
#include <openssl/cms.h>
```

```
const ASN1_OBJECT *CMS_get0_type(const CMS_ContentInfo *cms);
int CMS_set1_eContentType(CMS_ContentInfo *cms, const ASN1_OBJECT *oid);
const ASN1_OBJECT *CMS_get0_eContentType(CMS_ContentInfo *cms);
ASN1_OCTET_STRING **CMS_get0_content(CMS_ContentInfo *cms);
```

DESCRIPTION

CMS_get0_type() returns the content type of a CMS_ContentInfo structure as an ASN1_OBJECT pointer. An application can then decide how to process the CMS_ContentInfo structure based on this value.

CMS_set1_eContentType() sets the embedded content type of a CMS_ContentInfo structure. It should be called with CMS functions (such as CMS_sign, CMS_encrypt) with the CMS_PARTIAL flag and **before** the structure is finalised, otherwise the results are undefined.

ASN1_OBJECT ***CMS_get0_eContentType()** returns a pointer to the embedded content type.

CMS_get0_content() returns a pointer to the ASN1_OCTET_STRING pointer containing the embedded content.

NOTES

As the **0** implies **CMS_get0_type()**, **CMS_get0_eContentType()** and **CMS_get0_content()** return internal pointers which should **not** be freed up. **CMS_set1_eContentType()** copies the supplied OID and it **should** be freed up after use.

The ASN1_OBJECT values returned can be converted to an integer NID value using **OBJ_obj2nid()**. For the currently supported content types the following values are returned:

```
NID_pkcs7_data
NID_pkcs7_signed
NID_pkcs7_digest
NID_id_smime_ct_compressedData:
NID_pkcs7_encrypted
NID_pkcs7_enveloped
```

The return value of **CMS_get0_content()** is a pointer to the ASN1_OCTET_STRING content pointer. That means that for example:

```
ASN1_OCTET_STRING **pconf = CMS_get0_content(cms);
```

***pconf** could be NULL if there is no embedded content. Applications can access, modify or create the embedded content in a CMS_ContentInfo structure using this function. Applications usually will not need to modify the embedded content as it is normally set by higher level functions.

RETURN VALUES

CMS_get0_type() and **CMS_get0_eContentType()** return an ASN1_OBJECT structure.

CMS_set1_eContentType() returns 1 for success or 0 if an error occurred. The error can be obtained from [ERR_get_error\(3\)](#).

SEE ALSO

[ERR_get_error\(3\)](#)

COPYRIGHT

Copyright 2008–2019 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.