

NAME

RSA_print, RSA_print_fp, DSAParams_print, DSAParams_print_fp, DSA_print, DSA_print_fp, DHparams_print, DHparams_print_fp – print cryptographic parameters

SYNOPSIS

```
#include <openssl/rsa.h>

int RSA_print(BIO *bp, RSA *x, int offset);
int RSA_print_fp(FILE *fp, RSA *x, int offset);

#include <openssl/dsa.h>

int DSAParams_print(BIO *bp, DSA *x);
int DSAParams_print_fp(FILE *fp, DSA *x);
int DSA_print(BIO *bp, DSA *x, int offset);
int DSA_print_fp(FILE *fp, DSA *x, int offset);

#include <openssl/dh.h>

int DHparams_print(BIO *bp, DH *x);
int DHparams_print_fp(FILE *fp, DH *x);
```

DESCRIPTION

A human-readable hexadecimal output of the components of the RSA key, DSA parameters or key or DH parameters is printed to **bp** or **fp**.

The output lines are indented by **offset** spaces.

RETURN VALUES

These functions return 1 on success, 0 on error.

SEE ALSO

[BN_bn2bin\(3\)](#)

COPYRIGHT

Copyright 2000–2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at [<https://www.openssl.org/source/license.html>](https://www.openssl.org/source/license.html).