

NAME

pam_motd – Display the motd file

SYNOPSIS

pam_motd.so [*motd=/path/filename*]

DESCRIPTION

pam_motd is a PAM module that can be used to display arbitrary motd (message of the day) files after a successful login. By default the */etc/motd* file is shown. The message size is limited to 64KB.

OPTIONS

motd=/path/filename

The */path/filename* file is displayed as message of the day.

motd_dir=/path/dirname.d

The */path/dirname.d* directory is scanned and each file contained inside of it is displayed.

noupdate

Don't run the scripts in */etc/update-motd.d* to refresh the motd file.

When no options are given, the default is to display both */etc/motd* and the contents of */etc/motd.d*. Specifying either option (or both) will disable this default behavior.

MODULE TYPES PROVIDED

Only the **session** module type is provided.

RETURN VALUES

PAM_IGNORE

This is the only return value of this module.

EXAMPLES

The suggested usage for */etc/pam.d/login* is:

```
session optional pam_motd.so
```

To use a motd file from a different location:

```
session optional pam_motd.so motd=/elsewhere/motd
```

To use a motd file from elsewhere, along with a corresponding *.d* directory:

```
session optional pam_motd.so motd=/elsewhere/motd motd_dir=/elsewhere/motd.d
```

SEE ALSO

[motd\(5\)](#), [pam.conf\(5\)](#), [pam.d\(5\)](#), [pam\(7\)](#)

AUTHOR

pam_motd was written by Ben Collins <bcollins@debian.org>.

The **motd_dir=** option was added by Allison Karlitskaya <allison.karlitskaya@redhat.com>.